SEALED BID

CITY OF MOBILE

BID SHEET

Do Not Return Via Email or Fax

Mailing Address:

and correct invoice of completed order.

P. O. Box 1948 Mobile, Alabama 36633 (251) 208-7434 Purchasing Department and Package Delivery:

Government Plaza 4th Floor, Room S-408 205 Government St Mobile, Alabama 36644

This	is	Not	an	Order	
------	----	-----	----	-------	--

READ TERMS AND CONDITIONS ON REVERSE SIDE OF THIS PAGE BEFORE BIDDING

Typed by:	CII		Buyer:	02							
V-1	PI	ease quote the lo	west price at w	hich you will furnisl	h the article	s listed	below				
DATE	TE BID NO. DEPARTMENT Commoditi					ties to be delivered F.O.B. Mobile to:					
11/25/2020 5497 Motor Pool			Motor Pool		В	road Stre	et				
This bid	l must be rece	ived and stampe	d by the Purch	asing office not late	er than: 11:00	0 AM, F	riday, Dece	mber 11	, 2020		
QUANTITY	ARTICLE		orm ONLY. Make r al information requ	no changes on this form.	Attach	UNIT	UNIT PR		EXTENS	_	
QOANTIT	ANTIOLL	arry addition	ar information requ	area to this form.		ONT	Dollars	Cents	Dollars	Cents	
	3/4 TON	EXTENDED C	AB TRUCK V	VITH UTILITY BO	ODY						
Appx 2-8	_	provide chassis wi unted to chassis.	th Reading Mo	odel U98 Body, or e	qual,						
	CI.										
	Chassis Make		Model								
	Body		N. 6 - J - 1								
	wake		Model								
	Provide lite	rature and specific	cations on proc	luct bid.							
	State Warra	nty									
	Location of	Installation									
		s are $\frac{3}{4}$ Ton Extergines and C.A. of		sis with single rear v	wheels,						
	utility bodie		purchase up to	num of two (2) truck six (6) additional tr iis bid.							
		Pa	age 1 of 2								
				59-2							
77.							TOTA	L			
	ONE SIGNED C SED ENVELOP	OPY OF THIS BID		State delivery	time withir	1	_ days c	of rece	ipt of P	.0.	
IN ENGLO	SED ENVELUP	<u> </u>		Firm Name							
				Typed Sign:	ature						
We will allow	a discount	% 20 days fro	m date of receipt o								

- 1. All quotations must be signed with the firm name and by an authorized officer or employee.
- 2. Verify your bid before submission as it cannot be withdrawn or corrected after being opened. In case of error in extension of prices, the unit price will govern.
- 3. If you do not bid, return this sheet and state reason. Otherwise, your name may be removed from our mailing list.
- 4. The right is reserved to reject any, or all quotations, or any portions thereof, and to waive technicalities if deemed to be in the interest of the City of Mobile.
- 5. This bid shall not be reassignable except by written approval of the Purchasing Agent of the City of Mobile,
 - 6. State brand and model number of each item. All items bid must be new and latest model unless otherwise specified.
 - 7, If bid results are desired, enclose a self-addressed and stamped envelope with your bid. (All or None bids only)
 - 8. Do not include Federal Excise Tax as exemption certificate will be issued in lieu of same. The City is exempt from the Alabama and City sales taxes.
 - 9. PRICES ARE TO BE FIRM AND F.O.B. DESTINATION UNLESS OTHERWISE REQUESTED.
 - 10. BID WILL BE AWARDED ON ALL OR NONE BASIS UNLESS OTHERWISE STATED.
 - 11. Bids received after specified time will be returned un-opened.
 - 12. Failure to observe stated instructions and conditions will constitute grounds for rejection of your bid.
 - 13. Furnish literature, specifications, drawings, photographs, etc., as applicable with the items bid.
 - 14. Vendor May be required to obtain City of Mobile Business License as applicable to City of Mobile Municipal Code Section 34-50. For Business License inquiry contact the Revenue Department at (251) 208-7461 or cityofmobile.org/taxes.php.
 - 15. If a bid bond is required in the published specifications, see below: Each Bid Shall be Accompanied By A Cashier's Check, Certified Check, Bank Draft Or Bid Bond For the Sum Of Five (5) Percent Of The Amount Bid, Made Payable To The City Of Mobile And Certified By A Reputable Banking Institution. All Checks Shall Be Returned Promptly, Except The Check Of The Successful Bidder, Which Shall Be Returned After Fulfilling The Bid.
 - 16. Contracts in excess of \$50,000 require that the successful bidder make every possible effort to have at least fifteen (15) percent of the total value of the contract performed by socially and economically disadvantaged individuals.
 - 17. All bids/bid envelopes must have the bid number noted on the front. Bids that arrive unmarked and are opened in error shall be returned to vendor as an unacceptable bid.
 - 18. If successful vendor's principal place of business is out-of-state, vendor may be required to have a Certificate of Authority to do business in the State of Alabama from the Alabama Secretary of State prior to issuance of a Purchase Order. Vendors are solely responsible for consulting with the Secretary of State to determine whether a Certificate is required. See www.sos.alabama.gov/BusinessServices/ForeignCorps.aspx Please note that the time between application for and issuance of a Certificate of Authority may be several weeks.
 - 19. Vendors do not need a City of Mobile Business License or Certificate of Authority from the Alabama Secretary of State to submit a bid, but will need to obtain the Business License and Certificate of Authority, if applicable, prior to issuance of a Purchase Order.

BID CONTINUATION SHEET

Page_____ of____

OLIANTITY	Bid on this form ONLY. Make no changes on this form. Additional in-		UNIT PRICE		EXTENSION	
do Airiii	ARTICLES formation to be submitted on separate sheet and attached hereto.	UNIT	Dollars	Cents	Dollars	Cents
QUANTITY	Page 2 of 2 Price to be firm for a one (1) year period following the award of this bid. At the option of the City of Mobile and the successful vendor, the award of this bid may be extended for two (2) additional one (1) year periods. City of Mobile Business license required. See Item 14 on reverse. All vendors will be required to provide verification of enrollment in the E-Verify program. Additional information may be found at http://immigration.alabama.gov/ If the successful vendor's principal place of business is out-of-state, vendor may be required to have a Certificate of Authority to do business in the State of Alabama from the Secretary of State prior to issuance of a Purchase Order. Vendors are solely responsible for consulting with the Secretary of State to determine whether a Certificate is required. See: www.sos.alabama.gov/BusinessServices/ForeignCorps.aspx. Please note that the time between application for the issuance of a Certificate of Authority may be several weeks. Upon notification, vendor will have 10 business days to provide the Certificate of Authority and the E-Verify numbers to the Purchasing Department before award can be completed. (Vendors will possibly need to pay the expedite fee to meet this requirement because application is not sufficient. We must have a copy of the certificate with your Company ID number). Vendors do not need a City of Mobile Business License or Certificate of Authority from the Alabama Secretary of State, nor the E-Verify for certification to submit a bid, but will need to obtain the Business License and Certification to submit a bid, but will need to obtain the Business License and Certification of Authority verification and/or provide the E-Verify Certification, if applicable, prior to issuance of a Purchase Order.	UNIT		T		1000 6
	TO BE AWARDED ALL OR NONE					
			тот	TAL		
RETURN	ONE SIGNED CODY OF THIS CHOTATION - BEAD ABOVE INCTO	LIOTICS	10.0000			

RETURN ONE SIGNED COPY OF THIS QUOTATION IN ENCLOSED ENVELOPE

READ ABOVE INSTRUCTIONS BEFORE QUOTING

Firm Name	
Bv	

We will allow a discount _____ % 20 days from date of receipt of goods and correct invoice of completed order.

CHASSIS SPECIFICATIONS

		YES	NO
1.	¾ TON CHASSIS		
2.	EXTENDED CAB	-) .
3.	GASOLINE ENGINE	-	
4.	POWER WINDOWS, MIRRORS, AND DOOR LOCKS		
5.	SINGLE REAR AXLE		
6.	ALL WEATHER TIRES		
7.	AIR CONDITIONING		
8.	VINYL SEATS		
9.	CHASSIS COLOR TO BE WHITE		
10.	TOWING PACKAGE		
11.	SPARE TIRE WITH CRANK DOWN STORAGE		
12.	CAB TO AXLE – 56 INCHES		

BODY SPECIFICATIONS

The Following MINIMUM are for a utility body- to be installed on new CAB//CHASSIS with factory receiver hitch. Cab to axle measure is 56 inches. Utility body is 97.25 inches long x 76 inches wide.

	YES	NO
1. Body Shell - The body shell is to be constructed of 14-gauge two-sided A40 Galvanneal steel. The compartment tops and backs are to be a one-piece seamless design. All doors, door openings, drip rails, and other exposed steel edges are to be hemmed for strength, safety, and resistance to corrosion.		
2. Floor - The floor plate is to be constructed of a minimum of 12-gauge treadplate with a 13/8"return flange on each side. The side compartment back panel should overlap and interlock with the floor flange, providing support for the weight of the side compartment.	: 	:
3. Understructure - Cross sills are to be constructed from 11-gauge steel with 50,000 psi minimum yield strength.		
4. Tailgate - The tailgate is to be constructed of 14-gauge two-sided A40 Galvanneal steel. The tailgate is to be a <u>m</u> inimum of 12"high and be a slammable style.	±	
5. Doors - The doors are to be constructed of 20-gauge two-sided A40 Galvanneal steel. The doors are to be double paneled with hat section reinforcements.	=	-
6. Hinges - Corrosion resistant all stainless steel continuous hinges are to be installed to provide full length support for the doors and pry-proof security with a built-in weather shield. Hinges are to be spot welded to the door frames and must be supported with a six-year warranty.		-
7. Rotary Latches - Zinc plated corrosion resistant rotary latches are riveted to the doors with non-corrosive aluminum rivets incorporating stainless steel mandrels. The rotary latches are to be slam-latchable. The latching cam is to be elongated to allow the latch to move vertically relative to the lock strike to prevent torsional damage.		
8. Door Strikers - Adjustable strikers are to be affixed to the door frames with screws. (Welded-on door strikers are not acceptable.)		
9. Door Seals - Automotive "bulb type" neoprene door seals are to be installed by the manufacturer of the body on all door frames.		
10. Door Retainers - Double spring over center door retainers are to be installed on all vertical doors. Retainers need to hold doors in positive open or closed position. (Other types of retainers, like cables or chains, are not acceptable.)		

11. Shelving - Shelves are to be constructed of 18-gauge bright spangled galvanized steel. All shelves are to have hemmed dividers on 4" centers. Shelves need to have a minimum capacity rating of 250 lbs.		_
12. Shelving - 2 adjustable shelves with dividers street and curbside front vertical ladjustable shelf with dividers street and curbside rear vertical ladjustable shelf curbside horizontal.		_
13. Exterior Prime Paint - The body is to be completely immersed in electro deposition gray epoxy prime paint featuring a zinc phosphate pre coat and seal for additional corrosion protection. Prime paint is to be oven cured to provide a hard, durational corrosion protection.	able finish.	
14. Interior Paint - Interior paint is to be a mid-gloss, mar resistant, light gray finish.		_
15. Final Paint - Factory painted white inside of compartments and exterior of body.		
16. Undercoating - The body is to be completely undercoated by the body manufacturer using a water base acrylic.		=:
17. Installation - The manufacturer of the body is to supply a recommended installation process along with detailed installation instructions that conform to all applicable Federal Motor Vehicle Safety Standards. Rear body-to-chassis mounting brackets need to incorporate bumper support as well as provide FMVSS 301 protection. Furthermore, the manufacturer of the body is to supply an owner manual describing the proper care and maintenance of the body for the user.		
18. Warranty - The following items are to be covered by a <u>minimum six</u> (6) year limited warranty to the first owner/user of record.		
19. No Rust-Thru Guarantee		_
20. Continuous Door Hinges -Guaranteed not to fail to operate or come off product.		_
21. Latches and Lock Cylinders -Guaranteed against failure.		
22. Shelves -Guaranteed not to fail in bending under a maximum 250 lb. rated load.		
23. Lighting - Lighting is to meet all FMVSS standards. The wiring harness is to be encased in a plastic loom and all wires are to be colored for ease of troubleshooting. The wire harness must have connectors that are compatible with Ford, GM, and Dodge chassis without splicing. The stop/tail/tum and backup lights are to be recessed in the rear of the body. The stop/tail/tum lights are to be clear-back style. The side marker lights are to be recessed in the body drip rail for protection.		
24. Interior Compartment - The rear compartments are to be illuminated from clear back style taillights. All Lighting compartments are to be illuminated with lights powered off taillight circuit. Manual toggle switches are required on each light.		_

25. Lighting Wire - Wires must be retained by a fastening system.		
26. Retention Interior Light Guard and Warning Lights - Light guards are to be installed by the body manufacturer to provide protection for recessed stop/tail/turn, backup lights, and warning lights. The wiring harness needs to be protected also.		
27. Bumper - Drop step bumper with pintle recess cutout.		
28. Ladder rack Kargo master pipe rack constructed of 2" steel tubing, powder coated with a load rating of 1700 lbs. Cross bars are 62 inches wide.		
29. Bed liner Inside of body between compartments shall have a sprayed in bed liner applied. Spray in Bed liner shall be applied to the bottom of the open area as well as the sides up to the top of the compartments. Vendor shall also spray the tops of the compartments with the same Material as the sides and bottom of the center opening of the bottom. There shall be four (4) drain holes, one in each corner, each drain hole shall have an opening no less than %" open area after body has been painted and sprayed with spray in liner to allow for the drainage of rain and wash water		
30. There shall be four (4) drain holes, one in each comer, each drain hole shall have an opening no less than 3/4% open area after body has been painted and sprayed with spray in liner to allow for the drainage of rain and wash water.	— € 3	—
31. Four corner warning lights - Four (4) corner LED lights with rear round or square light heads recessed into the rear of the utility body Whelen brand LED or Equal – all LED with 5-year warranty. Front four (4) Corner Warning Lights shall not be installed in headlight/turn signal/parking light fixture. Any vehicle delivered with the front four corner warning lights installed in the headlight/turn signal/parking light fixtures will be refused and only accepted once vendor replaces the light fixture with the new ones.	— 9 8	
32. Chassis to be provided with crank down spare tire mount with tire. Vendor shall make sure that both items are accessible with the body bid by bidder.	= ;	



PROCUREMENT DEPARTMENT

Potential bidders are responsible to check this site for any ADDENDUMS that are issued. It is the responsibility of the BIDDER to check for, download, and include with their BID RESPONSE <u>any and all ADDENDUMS</u> that are issued for a specific BID published by the City of Mobile. Failure to download and include ADDENDUMS in your BID RESPONSE may cause your bid to be rejected.

This is a sealed bid. Any responses faxed or e-mailed will be rejected.

This is a sealed bid. Any response must be submitted in a sealed envelope with the bid number and bid opening date on the outside of the envelope.

Any response that arrives improperly marked or with no bid number and opening date on the outside of the delivery or express package and opened in error will be rejected and not considered.

It is the responsibility of the bidder to insure that their bid response is delivered to and received in the Purchasing Department <u>before</u> the date and time of the bid opening.

Be sure to read the Terms and Conditions. All bids are F.O.B. Destination unless otherwise stated.

Be sure to sign your bid!

Package/Bid Delivery Address: Purchasing Department 205 Government St. Room S408 Mobile, AL 36644

(Request First Delivery)