

Do Not Return Via Email or Fax

This is Not an Order

Mailing Address:
P. O. Box 1948
Mobile, Alabama 36633
(251) 208-7434

Purchasing Department
and Package Delivery:
Government Plaza
4th Floor, Room S-408
205 Government St
Mobile, Alabama 36644

READ TERMS AND CONDITIONS
ON REVERSE SIDE OF THIS PAGE
BEFORE BIDDING

Typed by: en Buyer: 006

Please quote the lowest price at which you will furnish the articles listed below

Table with columns: DATE (6/16/2021), BID NO. (5574), DEPARTMENT (Fire), Commodities to be delivered F.O.B. Mobile to: (To Be Specified)

This bid must be received and stamped by the Purchasing office not later than: 11:00 AM, Thursday, July 01, 2021

Main bid table with columns: QUANTITY, ARTICLES, UNIT, UNIT PRICE (Dollars, Cents), EXTENSION (Dollars, Cents). Includes detailed specifications for PROTECTIVE HELMET FOR STRUCTURAL FIREFIGHTING.

RETURN ONE SIGNED COPY OF THIS BID
IN ENCLOSED ENVELOPE

State delivery time within \_\_\_ days of receipt of P.O.

Firm Name \_\_\_\_\_

Typed Signature \_\_\_\_\_

By \_\_\_\_\_

We will allow a discount \_\_\_% 20 days from date of receipt of goods
and correct invoice of completed order.

1. All quotations must be signed with the firm name and by an authorized officer or employee.
2. Verify your bid before submission as it cannot be withdrawn or corrected after being opened. In case of error in extension of prices, the unit price will govern.
3. If you do not bid, return this sheet and state reason. Otherwise, your name may be removed from our mailing list.
4. The right is reserved to reject any, or all quotations, or any portions thereof, and to waive technicalities if deemed to be in the interest of the City of Mobile.
5. This bid shall not be reassignable except by written approval of the Purchasing Agent of the City of Mobile.
6. State brand and model number of each item. All items bid must be new and latest model unless otherwise specified.
7. If bid results are desired, enclose a self-addressed and stamped envelope with your bid. (All or None bids only)
8. Do not include Federal Excise Tax as exemption certificate will be issued in lieu of same. The City is exempt from the Alabama and City sales taxes.
9. PRICES ARE TO BE FIRM AND F.O.B. DESTINATION UNLESS OTHERWISE REQUESTED.
10. BID WILL BE AWARDED ON ALL OR NONE BASIS UNLESS OTHERWISE STATED.
11. Bids received after specified time will be returned un-opened.
12. Failure to observe stated instructions and conditions will constitute grounds for rejection of your bid.
13. Furnish literature, specifications, drawings, photographs, etc., as applicable with the items bid.
14. Vendor May be required to obtain City of Mobile Business License as applicable to City of Mobile Municipal Code Section 34-50. For Business License inquiry contact the Revenue Department at (251) 208-7461 or [cityofmobile.org/taxes.php](http://cityofmobile.org/taxes.php).
15. If a bid bond is required in the published specifications, see below:  
Each Bid Shall be Accompanied By A **Cashier's Check, Certified Check, Bank Draft Or Bid Bond** For the Sum Of Five (5) Percent Of The Amount Bid, Made Payable To The City Of Mobile And Certified By A Reputable Banking Institution. All Checks Shall Be Returned Promptly, Except The Check Of The Successful Bidder, Which Shall Be Returned After Fulfilling The Bid.
16. Contracts in excess of \$50,000 require that the successful bidder make every possible effort to have at least fifteen (15) percent of the total value of the contract performed by socially and economically disadvantaged individuals.
17. All bids/bid envelopes must have the bid number noted on the front. Bids that arrive unmarked and are opened in error shall be returned to vendor as an unacceptable bid.
18. If successful vendor's principal place of business is out-of-state, vendor may be required to have a Certificate of Authority to do business in the State of Alabama from the Alabama Secretary of State prior to issuance of a Purchase Order. Vendors are solely responsible for consulting with the Secretary of State to determine whether a Certificate is required. See [www.sos.alabama.gov/BusinessServices/ForeignCorps.aspx](http://www.sos.alabama.gov/BusinessServices/ForeignCorps.aspx). Please note that the time between application for and issuance of a Certificate of Authority may be several weeks.
19. Vendors do not need a City of Mobile Business License or Certificate of Authority from the Alabama Secretary of State to submit a bid, but will need to obtain the Business License and Certificate of Authority, if applicable, prior to issuance of a Purchase Order.

BID CONTINUATION SHEET

QUANTITY	ARTICLES	UNIT	UNIT PRICE		EXTENSION	
			Dollars	Cents	Dollars	Cents
	<p style="text-align: center;">Page 2 of 2</p> <p>If the successful vendor's principal place of business is out-of-state, vendor may be required to have a Certificate of Authority to do business in the State of Alabama from the Secretary of State prior to issuance of a Purchase Order.</p> <p>Vendors are solely responsible for consulting with the Secretary of State to determine whether a Certificate is required. See: <a href="http://www.sos.alabama.gov/BusinessServices/ForeignCorps.aspx">www.sos.alabama.gov/BusinessServices/ForeignCorps.aspx</a>. Please note that the time between application for the issuance of a Certificate of Authority may be several weeks.</p> <p>Upon notification, vendor will have 10 business days to provide the Certificate of Authority and the E-Verify numbers to the Purchasing Department before award can be completed. (Vendors will possibly need to pay the expedite fee to meet this requirement because application is not sufficient. We must have a copy of the certificate with your Company ID number).</p> <p>Vendors do not need a City of Mobile Business License or Certificate of Authority from the Alabama Secretary of State, nor the E-Verify for certification to submit a bid, but will need to obtain the Business License and Certificate of Authority verification and/or provide the E-Verify Certification, if applicable, prior to issuance of a Purchase Order.</p> <p>State of Alabama Local Vendor Preference Law 41-16-50 (a) and (d) will apply to this purchase.</p> <p>If you have any questions, please feel free to contact the Purchasing Department at <a href="mailto:purchasing@cityofmobile.org">purchasing@cityofmobile.org</a>.</p> <p><b>TO BE AWARDED ALL OR NONE</b></p>					
			TOTAL			

**RETURN ONE SIGNED COPY OF THIS QUOTATION IN ENCLOSED ENVELOPE**

**READ ABOVE INSTRUCTIONS BEFORE QUOTING**

Firm Name \_\_\_\_\_

By \_\_\_\_\_

We will allow a discount \_\_\_\_\_% 20 days from date of receipt of goods and correct invoice of completed order.

## **FIRE HELMET PRODUCT SPECIFICATION**

### **GENERAL:**

Helmets manufactured in accordance with this specification are designed to mitigate adverse environmental effects to the firefighter's head while providing the specifying authority with what are, in their opinion, essential requirements.

### **WEIGHT:**

All helmets shall be less than 3.5 pounds with the following options installed: Retractable face shield, eagle front holder, chin strap, edge beading, reflective trapezoids, comfort liner, and head suspension.

### **PERFORMANCE CRITERIA/STANDARDS:**

Traditional Fire Helmets shall meet the requirements of NFPA 1971:2018 (or the current edition) for structural firefighting and proximity firefighting when that option is selected; US-OSHA 1910.156, and CAL-OSHA.

All eye/face protection sold as part of the original helmet assembly shall be compliant with the impact requirements of the current editions of ANSI/ISEA Z87.1 and NFPA 1971.

### **PERFORMANCE VERIFICATION DATA REQUIREMENT:**

Response to this specification shall include a complete and current NFPA 1971 test report from a recognized, accredited test facility detailing all performance data for the helmet(s) and compliant helmet components included in the original assembly. Certificates of conformance and/or letters of certification alone shall not be acceptable. Component testing is not acceptable. Certification testing is conducted every year to a random lot size, as per NFPA requirements.

### **MANUFACTURER'S WARRANTY:**

Fire Helmets to be free from defects in materials and/or faulty workmanship for a period of ten (10) years from the date of manufacture.

### **HELMET SHELL:**

Traditional Fire Helmets shall have a classic American Fire Service style helmet shell, comprising a crown, with four (4) major ribs (front, back, left and right sides), and four minor ribs equidistant between each major rib, and a brim that has a short front visor continuing around the sides to a large rear watershed area. The upper surface of the watershed shall have a textured finish with ivy scroll on the back of the watershed brim. The underside of the brim shall have drill guides for the various eye/face protection that can be attached to the shell.

The shell material shall be a fiberglass composite, consisting of a high-temperature-, flame-, and chip-resistant "through-colored" thermoset resin, reinforced with 1" and 2" chopped fiberglass, compression-molded to form a one-piece shell. The shell shall be available in white, red, black, and yellow with an unpainted, matte finish. The shell dimensions (with edge-trim) shall be 15.5" in length, 11.88" in width and a crown depth of 6.5". The shell shall have a nominal wall thickness of 0.065" in the crown and 0.080" in the brim. The shell shall have black or white<sup>1</sup>, high-temperature, flame-resistant, flexible edge trim made of thermoplastic rubber (TPR) with an aluminum core. The edge-trim is secured around the entire brim of the helmet by crimping the aluminum core, which simultaneously captures and retains a wire used to reinforce the brim of the helmet. The edge-trim is secured at the mating ends with a high temperature adhesive and clamped by the helmet hanger clip at the edge of the rear brim.

The shell shall have a helmet hanger comprised of a 3/4", nickel plated "D" ring and a stainless-steel clip. The helmet hanger shall be attached to the center rear of the brim.

**FRONT HOLDER:**

The helmet shell shall be furnished with a collapsible brass front-piece holder designed to absorb impact that shall be attached to the main rib on the shell front, and positioned to capture the top of standard 6" fire department identification shields (i.e., front piece). The front holder shall be a brass carved eagle.

The shell shall have a thermoplastic, front-piece mounting bracket affixed to the front center of the brim. The bracket shall provide for positioning and retention of 6" front pieces.

**IMPACT CAP:**

The impact cap is designed to help provide increased thermal and impact protection. The impact cap shall be an impact-resistant polymer liner covered by a rigid cell, high temperature, energy absorbing urethane foam cap that covers the entire inner crown of the helmet. This impact cap is held into the helmet shell by the Shell Release tabs and corresponding brackets. It shall be removable for inspection and replacement.

**HEAD SUSPENSION:**

Traditional Fire Helmet shall consist of a six-way head suspension system, attached to the impact cap. The head suspension system comprises three (3) fixed 0.75" wide nylon straps mounted at six points on the impact liner and fastened at their intersection to form the 6-way overhead strap assembly. The straps are attached to the impact cap by means of a rigid plastic clip that locks the straps into the lugs of the impact cap liner. A cloverleaf crown pad shall be incorporated into the overhead strap assembly.

**SHELL RELEASE SYSTEM:**

The impact liner, complete with suspension system and chinstrap assembly (as described under "CHINSTRAP") shall be retained to the helmet shell by means of two (2) thermoplastic retention clips mounted under the eye/face protection hardware. This design will enable the shell to be released from the helmet when impacted from below the brim, reducing the chance of being injured by the chinstrap, and leaving the impact cap on the wearer's head for continued thermal and impact protection.

**SIZING ADJUSTMENT:**

The size of the headband may be adjusted to fit the wearer's head by means of a ratchet adjustment system. The headband is attached to the sides of the impact cap liner by four (4) flexible retention tabs.

The rear ratchet arms shall have three (3) adjustable positions so that the angle of the ratchet may be set to accommodate the nape of the wearer's head. The headband height shall be adjustable at the front of the helmet via a hook and loop system to provide additional comfort to the wearer and maximize compatibility with the SCBA facepiece.

The headband shall have a head size range of 6 3/8 to 8 3/4, adjustable in 1/8" increments.

**COMFORT LINER:**

Traditional Fire Helmet shall have a removable comfort liner, consisting of a headband cushion and a ratchet pad. Both components made of a foam-core laminate system, comprised of a soft black flame-resistant flannel material against the user's head backed by a soft loop material secured to the headband and ratchet with hook fastener. The comfort liner shall be machine washable.

**CHINSTRAP:**

The chinstrap shall be constructed of three (3) pieces (or sections) of 3/4" wide, spun-Nomex webbing, which are connected by a high-temperature, durable thermoplastic quick-release buckle on the left side of the helmet, and by a cast zinc postman's slide buckle on the right side of the helmet. The middle section shall be a minimum of 23" in length and the total length of the chinstrap shall be 35" at full extension, end to end.

**EAR/NECK PROTECTION:**

Traditional Fire Helmet provides ear and neck protection with a 7.25" wide, 19" long

The triple-layer earlap shall consist of a 4.5 oz. / yd., black colored Nomex outer layer, and two flame resistant black flannel inner layers. The earlap shall be secured via two (2) Velcro tabs at either end of the top of the earlap and one continuous length of Velcro along the top edge of the earlap.

The earlap shall be machine washable. The ear and neck protector shall be removable without interfering with the overhead strap assembly in any way and without removing any part of the helmet suspension.

**RETRO-REFLECTIVE TRIM:**

Traditional Fire Helmet shall have eight (8) tetrahedron shaped pieces of retro-reflective trim around the exterior crown of the helmet shell for maximum visibility. Reflexite Lime-Yellow trim shall be installed.



## PROCUREMENT DEPARTMENT

Potential bidders are responsible to check this site for any **ADDENDUMS** that are issued. It is the responsibility of the **BIDDER** to check for, download, and include with their **BID RESPONSE** any and all **ADDENDUMS** that are issued for a specific **BID** published by the City of Mobile. Failure to download and include **ADDENDUMS** in your **BID RESPONSE** may cause your bid to be rejected.

This is a sealed bid. Any responses faxed or e-mailed will be rejected.

This is a sealed bid. Any response must be submitted in a sealed envelope with the bid number and bid opening date on the outside of the envelope.

Any response that arrives improperly marked or with no bid number and opening date on the outside of the delivery or express package and opened in error will be rejected and not considered.

It is the responsibility of the bidder to insure that their bid response is delivered to and received in the Purchasing Department before the date and time of the bid opening.

Be sure to read the Terms and Conditions. All bids are F.O.B. Destination unless otherwise stated.

Be sure to sign your bid!

Package/Bid Delivery Address:  
Purchasing Department  
205 Government St. Room S408  
Mobile, AL 36644

(Request First Delivery)