SEALED BID

CITY OF MOBILE

BID SHEET

This is Not an Order

Do Not Return Via Email or Fax

Mailing Address: P. O. Box 1948 Mobile, Alabama 36633 (251) 208-7434

We will allow a discount _____

and correct invoice of competed order

__% 20 days from date of receipt of goods

Purchasing Department and Package Delivery:

Government Plaza
4th Floor, Room S-408
205 Government St.
Mobile, Alabama 36644
Postal Service Does Not Deliver to This Street Address

READ TERMS AND CONDITIONS ON REVERSE SIDE OF THIS PAGE

BEFORE BIDDING

Typed by:	en		Buyer: 002						
	Plea	se quote the lowe	est price at which you will fu	rnish the articles	liste	d below			
DATE		BID NO.	DEPARTMENT	Commodities	to be c	eliverd F.O.	B. Mobi	e to:	
04/15/2	024	5877	Motor Pool			As S	pecifie	i	
This bid m	ust be received	d and stamped by the	e Purchasing office not later tha	n:	12:0	l PM, Fri	day, N	Iay 3, 20	24
QUANTITY	ARTICLES		ONLY. Make no changes on this form rmation required to this form.	n. Attach	UNIT	UNIT PR	CE Cents	EXTENS Dollars	SION
Appx 2-10	Current mode Wet Line K attached spource I was attached spource I was attached spource I with Hydraulic K I was a with Hydrau Include cost FOB Mobil City of Mode I was attached spource I was attached spourc	del Cab and Chassis Lit and Trailer Towin ecifications. Make Mak	tions on product bid. hase a minimum of two (2) Cab and Trailer Towing Packages. e in the price of the vehicle. Price	and Chassis cing to be vard of e award of					
		•		_		ТОТ	AI		
		OPY OF THIS BID	State de	livery time withi	n L			eipt of F	<u> </u>
	ED ENVELOR			•	_	_ ,		•	
Phone Numb	oer			ame					
Email Addres	ss		Signati	ure					

Type or Print Name

- 1. All quotations must be signed with the firm name and by an authorized officer or employee.
- Verify your bid before submission as it cannot be changed or corrected after being opened. In case of error in extension of prices, the unit price will govern.
- 3. If you do not bid, return this sheet and state reason. Otherwise, your name may be removed from our mailing list.
- 4. The right is reserved to reject any, or all quotations, or any portions thereof, and to waive technicalities if deemed to be in the interest of the City of Mobile.
- 5. This bid shall not be reassignable except by written approval of the Purchasing Agent of the City of Mobile.
- 6. State brand and model number of each item. All items bid must be new and latest model unless otherwise specified.
- 7. If bid results are desired, enclose a self-addressed and stamped envelope with your bid. (All or None bids only)
- 8. Do not include Federal Excise Tax as an exemption certificate will be issued in lieu of same. The City is exempt from the State of Alabama and City sales taxes.
- 9. PRICES ARE TO BE FIRM AND F.O.B. DESTINATION UNLESS OTHERWISE REQUESTED.
- 10. BID WILL BE AWARDED ON ALL OR NONE BASIS UNLESS OTHERWISE STATED.
- 11. Bids received after specified time will be returned un-opened.
- 12. Failure to observe stated instructions and conditions will constitute grounds for rejection of your bid.
- 13. Furnish literature, specifications, drawings, photographs, etc., as applicable with the items bid.
- 14. Vendor may be required to obtain City of Mobile Business License as applicable to City of Mobile Municipal Code Section 34-50. For Business License inquiry, contact the Revenue Department at (251) 208-7462 or cityofmobile.org/business-license-overview/
- 15. IF a bid bond is required in the published specifications, see below: Each bid shall be accompanied by a Cashier's Check, Certified Check, Bank Draft or Bid Bond for the sum of five (5) Percent of the amount bid, made payable to the City of Mobile and certified by a reputable banking institution. All checks shall be returned promptly, except the check of the successful bidder, which shall be returned after fulfilling the bid.
- 16. Contracts in excess of \$50,000 require that the successful bidder make every possible effort to have at least fifteen (15) percent of the total value of the contract performed by socially and economically disadvantaged individuals.
- 17. All bids/bid envelopes must have the bid number noted on the front. Bids that arrive unmarked and are opened in error shall be returned to vendor as an unacceptable bid.
- 18. If successful vendor's principal place of business is out-of-state, vendor may be required to have a Certificate of Authority to do business in the State of Alabama from the Alabama Secretary of State prior to issuance of a Purchase Order. Vendors are solely responsible for consulting with the Secretary of State to determine whether a Certificate is required. See www.sos.alabama.gov/BusinessServices/ForeignCorps.aspx. Please note that the time between application for and issuance of a Certificate of Authority may be several weeks.
- 19. Vendors do not need a City of Mobile Business License or Certificate of Authority from the Alabama Secretary of State to submit a bid, but may need to obtain the Business License and Certificate of Authority if applicable, prior to issuance of a Purchase Order.
- Bids and addendums are posted at www.cityofmobile.org/services/business/bids/. It is the responsibility of the vendor to check the City's bid page for updates and addendums.
- 21. Vendors must be able to provide the following upon request. Federal W-9 form, proof of registration in the E-Verify program, and Certificate of Authority to do business in Alabama/Registration with the Alabama Secretary of State within 24 hours of request.
- 22. City of Mobile applies local vendor preference to all purchases: Code of Aabama, 1975, Sections 41-16-50(a) and 41-16-50(d), except federally funded grants.
- 23. Equal Employment Opportunity. Except as otherwise provided under 41 CFR part 60, all contracts that meet the definition of "federally assisted construction contract" in 41 CFR Part 60-1.3 must include the equal opportunity clause provided under 41 CFR 60-1.4(b), in accordance with Executive Order 11246, "Equal Employment Opportunity" (30 FR 12319, 12935, 3 CFR Part, 1964-1965 Comp., p. 339), as amended by Executive Order 11375, "Amending Executive Order 11246 Relating to Equal Employment Opportunity," and implementing regulations at 41 CFR part 60, "Office of Federal Contract Compliance Programs, Equal Employment Opportunity, Department of Labor."
- 24. Davis-Bacon Act, as amended (40 U.S.C. 3141-3148) will apply when required by Federal program regulations.

BID CONTINUATION SHEET

Page____ of____

QUANTITY	ARTICI FS Bid on this form ONLY. Make no changes on this form. Additional	LINIT	UNIT PRICE	EXTENSION
QOZIVIII	information to be submitted on separate sheet and attached hereto.	UNIT	Dollars Cents	Dollars Cents
QUANTITY	ARTICLES Bid on this form ONLY. Make no changes on this form. Additional information to be submitted on separate sheet and attached hereto. Page 2 of 2 All vendors will be required to provide verification of Enrollment in the E-Verify program. Additional information may be found at http://immigration.alabama.gov/ If the successful vendor's principal place of business is out-of-state, Vendor may be required to have a Certificate of Authority to do Business in the State of Alabama from the Secretary of State prior to issuance of a Purchase Order. Vendors are solely responsible for consulting with the Secretary of State to determine whether a Certificate is required. See: www.sos.alabama.gov/BusinessServices/ForeignCorps.aspx . Please note that the time between application for the issuance of a Certificate of Authority may be several weeks. Upon notification, vendor will have 10 business days to provide the Certificate of Authority and the E-Verify numbers to the Purchasing Department before award can be completed. (Vendors will possibly need to pay the expedite fee to meet this requirement because application is not sufficient. We must have a copy of the certificate with your Company ID number). Vendors do not need a City of Mobile Business License or Certificate of Authority from the Alabama Secretary of State, nor the E-Verify for certification to submit a bid, but will need to obtain the Business License and Certificate of Authority verification and/or provide the E-Verify Certification, if applicable, prior to the award of this bid. State of Alabama Local Vendor Preference Law 41-16-50 (a) and (d) will apply to this purchase.	UNIT		
	CONE OF SILENCE. From the time of advertising, and until the final award by completion of a signed contract or purchase document issued by the City, there is a prohibition on communication by respondents (or anyone on their behalf) with the City staff and elected officials regarding this request for bids, proposals, or qualifications. This does not apply to communications directly with the Procurement Department staff during authorized question periods, or with designated City staff during pre-bid conferences, interviews, requests for clarification, and written contract negotiations. Breaking the established prohibition on communication, if proven, may result in a disqualification of your submittal. If you have any questions, please feel free to contact the Purchasing Department at 251-208-7434 or purchasing@cityofmobile.org.			
			TOTAL	
			TOTAL	

RETURN ONE SIGNED COPY OF THIS QUOTATION IN ENCLOSED ENVELOPE

READ ABOVE INSTRUCTIONS BEFORE QUOTING

Firm Name		
Ву		

We will allow a discount ______ % 20 days from date of receipt of goods and correct invoice of competed order.

2024 or Newer Shuttle Truck with the following MINIMUM specifications:

		Yes	No
GEN	ERAL		
1.	AXLE CONFIGURATION 4X2		
2.	GVWR Rating 33,000		
3.	DIMENSIONS: Wheelbase=152" CA=84" AF=60"	-	
4.	CHASSIS SPECIFICATIONS- Submit complete chassis specifications		
	Sheet.		:
FR	AME		
1.	TOW HOOKS, FRONT (2) Frame Mounted		
2.	FRAME RAILS Heat Treated Alloy Steel (120,000 PSI Yield); 10. 125" x 3.580"X 0.312", Minimum RBM 1,700,000. Frame assembly huck bolts only. No threaded bolts. No tapered rails.	·	
3.	BUMPER, FRONT Contoured, Steel, Powder Coated		
FRO	NT AXLE AND SUSPENSION		
1.	AXLE, FRONT NON-DRIVING 12,000-lb Capacity Minimum. Meritor MFS-12-122A or equal.	N 	
2.	SUSPESION, FRONT, SPRING Parabolic Taper Leaf, Shackle Type, 12,000-lb Capacity Minimum, with Shock Absorbers.		
BRAJ	KES		
1.	BRAKE SYSTEM AIR Dual System for Straight Truck Applications	8-	-
2.	AIR BRAKE ABS (Bendix Antilock Brake System or equal) Full Vehicle Wheel Control System (4-Channel)	5 <u></u>	

3.	TRAILER CONNECTIONS Four-wheel, with Hand Control Valve and Tractor Protection Valve, for Straight Truck		
4,	AIR DRYER Bendix AD-IP with Heater		
5,	AUTOMATIC SLACK ADJUSTERS Font and Rear		
6	NON-ASBESTOS BRAKE LININGS Front and Rear		
7.	BRAKES, FRONT, AIR CAM S-Cam; 15.0" x 4.0"; 20 Sq. In. Long Stroke Brake Chambers		
8.	BRAKES, REAR, AIR CAM S-Cam; 16.5" x 7.0", 30/30 Sq. In. Long Stroke Brake Chamber and Spring Actuated Parking Brake		
9.	AIR COMPRESSOR 18.7 CFM	t 	
10). AIR DRYER LOCATION Mounted Outside Right Rail, Forward of Front Wheel	<u> </u>	-
1	1. AIR TANK LOCATION (2) Mounted Under Battery Box, Outside left Rail, Under Cab (1) Mounted Parallel Under Left Frame Rail		E
STEI	ERING		
1.	STEERING COLUMN Tilting		
2.	STEERING WHEEL 4-Spoke; 18" Dia., Black	-	
3.	STEERING GEAR Power (Sheppard M100 or equal)	:	
DRIV	VELINE		
1.	DRIVELINE SYSTEM Dana Spicer 1710 or equal, for 4x2 Axle Configuration		
EXH	AUST SYSTEM		
1.	EXHAUST SYSTEM Single, Horizontal After treatment Device, Frame Mounted Under Right Rail Forward Location, Includes Single Short Horizontal Tail Pipe		

ELECTRICAL SYSTEMS

1.	ELECTRICAL SYSTEM 12-Volt, Standard equipment to include: Data Link Connector for vehicle programming and diagnostics, Integral headlight Dimmer Switch with Turn Lever, Integral Parking Light with Front Turn Signal and Rear Tail Light, Electric Key Operated Starter Switch, Dual Combination Stop, Turn Tail and Back Up Lights with Reflector, Self-Cancelling Turn Signal Switch with Lane Change Feature, Flush Mounted Front Turn Signals including Reflectors and Auxiliary Side Turn Signals, Solid State Flashers. All lighting can be LED		
2.	ALTERNATOR Brush Type; 12 volt Minimum 160 Amp. Capacity, Pad Mount, with Remote Voltage Sensor		
3.	BATTERY BOX Steel, with Plastic Cover, 2-3 Battery Capacity, Mounted Left Side Under Cab		
4.	BATTERY SYSTEM Maintain-Free, (2) 12-Volt 1320CCA Total Minimum, Top Threaded Stud		
5.	BODY BUILDER WIRING To Rear of Frame, with Stop, Tail, Turn, and Marker Lights Circuits, Ignition Controlled Auxiliary Feed and Ground, Less Trailer Socket	:	
6.	CIRCUIT BREAKERS Manuel- Rest (Main Panel) SAE Type III with Trip Indicators, Replaces All Fuses	1	
7.	RADIO AM/FM/WB/Clock/ 3.5MM Auxiliary Input		
8.	Speakers (2) 6.5" Dual Cone Mounted in Doors		
9.	HORN, ELECTRIC Disc Style		
10.	HORN, AIR Black, Single, Trumpet, With Lanyard Pull Cord		
11.	HEADLIGHTS LED, Composite Aero Design	-	
12.	STARTING MOTOR 12-Voly, with Soft-Start	-	

FRON	NT END		
1.	GRILLE Stationary Chrome		
2.	FRONT END Tilting, Fiberglass, with Three Piece Construction		
PAIN	T & KEYS		
1.	PAINT SCHEMATIC, Single Color, White		
2.	PAINT TYPE: Base Coat/Clear Coat, To protect paint from fading and minor Scratches		
3.	KEYS-Door and Ignition keys should be the same. Provide 4 fully functional keys per truck.		
ENGI	NE		
1.	ENGINE, DIESEL, (6.7 Cummins Only) In-Six Cylinder Only, Minimum @2400 RPM, Minimum 660 lbft Torque @1600	1260HP	
2.	RADIATOR Aluminum; 2-Row, Cross Flow, Over Under System, 717 Sq. In Louvered, with 313 Sq. In Charge Air Cooler with In-Tank Transmission Cooler		
3.	FAN DRIVE Viscous Type, Screw On		
4.	AIR CLEANER with Service Protection Element		2
5.	ANTI-FREEZE Red, Extended Lift Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection		
6.	FEDERAL EMISSIONS EPA, OBD and GHG Certified for Calendar Year 2020	N 	
7.	THROTTLE, HAND CONTROL Engine Speed Control for PTO: Electronic, Stationary Pre-Set, Two Speed Settings; Mounted on Steering Wheel		

8.	ENGINE CONTROL, REMOTE MOUNTED Provision for; Includes Wiring for Body Builder Installation of PTO Controls; with Ignition Switch Control		
TRAN	ISMISSION		
1.	TRANSMISSION, AUTOMATIC (Allison 3000 RDS) 5 TH Generation Controls, Close Ratio, 5-Speed with Overdrive, with PTO Provision, Less Retarder, Includes Oil Level Sensor, with 80,000-lb GVW and GCW Max, On/Off Highway		
2.	TRANIMISSION SHIFT CONTROL: Column Mounted Stalk Shifter or equal		
3.	TRANSMISSION OIL Synthetic		
4.	ALLISON SPARE INPUT/OUTPUT for Rugged Duty Series (RDS); General Purpose Trucks, Construction		<u></u>
5.	SHIFT CONTROL PARAMETERS Allison 3000 Series Transmissions, 5 th Generation Controls, Performance Programming	190	
6.	NEUTRAL AT STOP Allison Transmission Shifts to Neutral When Service Brake is Depressed and Vehicle is at stop; Remains in Neutral Until Service Brake is Released		
7.	PTO LOCATION Customer Intends to Install PTO at Left Side of Transmission		
REAF	R AXLE AND SUSPENSION		
1.	AXLE, REAR, SINGLE (Dana Spicer S140 or equal) Single Reduction, 21,000-lb Capacity 190 Wheel Ends. Gear Ration TBD.	·	4
2.	SUSPENSION, REAR, SINGLE 23,500-lb Capacity, Vari-Rate Springs, with 4500-lb Capacity Auxiliary Rubber Springs		
FUEL	SYSTEM & TANKS		
1.	FUEL TANK Top Draw, Non-Polished Aluminum, D-Style, 16" Tank Depth 50 US Gallon Canacity Mounted Right Side, Under Cab		

2.	DEF TANK 7 US Gallon Capacity, Frame Mounted Outside Left Rail, Under Cab		
3.	3. FUEL /WATER SEPERATOR 12 VDC Electric Heater, Includes Pre-Heater, Includes Water-in-Fuel Sensor. Engine mount preferred.		
CAB			
1.	CAB Conventional, Day Cab. Galvanized steel construction.	· · · · · · · · · · · · · · · · · · ·	
2.	AIR CONDITIONER with Integral Heater & Defroster.		
3.	GAUGE CLUSTER Base Level; English with English Speedometer and Tachometer, For Air Brake Chassis, Includes Engine Coolant Temperature Primary and Secondary Air Pressure, Fuel and DEF Gauges, Oil Pressure Gauge, Includes 3 Inch Monochromatic Text Display	,	
4.	INSTRUMENT PANEL CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster		
5.	SEAT, DRIVER, (National 2000 or equal) Air Suspension, High Back with Integral Headrest, Vinyl, Isolator, 1 Chamber Lumbar, With 2 Position Front Cushion Adjust, -3 to +14 Degree Angle Back Adjust		
6.	SEAT, TWO-MAN PASSENGER (National) Fixed Back, Integrated Headrest in Both Occupant Positions, Vinyl, with Under Seat Storage Compartment	, .	
7.	SEAT BELTS, High Visibility Orange		
8.	MIRRORS (2) C-Loop, Power Adjustable, Heated, Back Black Heads, Brackets and Arms, 7.5" x 14." Flat Glass, Includes 7.5" x 7" Convex Mirrors, for 102" Load Width		
9.	MIRRORS, CONVEX HOOD MOUNTED (2) Right and Left Sides, Black 7.5" Sq.		
10.	CAB INTERIOR TRIM Classic, for Day Cab		-
11.	CAR REAR SUSPENSION Rubber Suspension, for Low Cab Height		
12.	WINDOW, POWER (2) and Power Door Locks, Left and Right Doors. Includes express down feature.		

13	. ACCESS, CAB Steel, Driver & Passenger Sides, Two Steps per Door	·
WHE	ELS & TIRES	
1.	WHEELS, FRONT DISC; 22.5X8.25 Rims, Painted Steel with White Powder Coat Paint, 2- Hand Hole, 10- Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, With Steel Hubs	
2.	TIRE, FRONT 11R22.5 Load Range G< 75 MPH, Continental ECO Plus HS3 or equal	
3.	Front Wheel Bearings Oil Lubricated ILO Standard. Stemco Voyager or Equal	· · · · · · · · · · · · · · · · · · ·
4.	WHEELS, REAR DUAL DISC; 22.5X8.25 Rims, Painted Steel with White Powder Coat Paint, 2-Hand Hole, 10-Stud, 285.75mm BC, Hud-Piloted, Flanged Nut, with Steel Hubs	e
5.	TIRE, REAR 11R22.5 Load Range G, 75 MPH, Continental HDR2 or equal. For On-Off Road service	
TOW	PACKAGE TO CONFIGURED AS	
1.	WETLINE KIT to include transmission mount PTO, hydraulic pump, hydraulic oil tank, Hydraulic Return filter on lines from the trailer and another filter between the tank and t the pump inlet, hydraulic relief valves, operator controls, headache rack, concrete weight Box, electrical junction box, trailer connections, safety chain two (2) D-Rings, diamond tread Fabricated rear axle wheel panel covers and mud flaps. All painted surfaces black. Horizontal red and white reflective tape on the rear wheel mud flap holders	
	Hydraulic oil tank shall be no smaller than 20 inches wide x 20 inches tall x 15 inches deep. Tank shall have quarter turn cut off valves at the outlet and inlet to the tank. These valves shall be plumbed into the tank. The valves shall be accessible from side of truck via rods with "D" Handles.	
2.	PTO on/off switch must be assessable from standing outside of truck	

3. PINTLE HITCH to be SAF-Holland model/part # PH-210RD11 NO SUBSTITUTE Hitch shall be mounted such that the center point of the hitch is 37 inches from the ground. Hitch mounting shall be able to handle 90,000 pounds.	
Vendor to supply pictures of proposed wet line kit if requested	¥ (<u> </u>
CONCRETE WEIGHT BOX shall be provided empty but secured to the chass Box size shall be no less than 16" tall, 48" long and 23" wide. Vendor shall provide a formed lid that will fit over the concrete weight box. Lid not to be attached. City will fill the box and attach the lid Weight box shall be mounted over the center of the rear axle	is.
Tow package Must be approved before manufactured and installed	=======================================
WARRANTY- Include in Bid Price- Provided documentation of coverage included bid submittal.	d with
WARRANTY Standard for Engine, Cab and Chassis	_
OWNERS MANUAL – Printed and Electronic copy.	



PROCUREMENT DEPARTMENT

Potential bidders are responsible to check this site for any ADDENDUMS that are issued. It is the responsibility of the BIDDER to check for, download, and include with their BID RESPONSE any and all ADDENDUMS that are issued for a specific BID published by the City of Mobile. Failure to download and include ADDENDUMS in your BID RESPONSE may cause your bid to be rejected.

This is a sealed bid. Any responses faxed or e-mailed will be rejected.

This is a sealed bid. Any response must be submitted in a sealed envelope with the bid number and bid opening date on the outside of the envelope.

Any response that arrives improperly marked or with no bid number and opening date on the outside of the delivery or express package and opened in error will be rejected and not considered.

It is the responsibility of the bidder to ensure that their bid response is delivered to and received in the Purchasing Department <u>before</u> the date and time of the bid opening.

Be sure to read the Terms and Conditions.
All bids are F.O.B. destination unless otherwise stated.

Be sure to sign your bid!

Package/Bid Delivery Address: Purchasing Department 205 Government St. Room S408 Mobile, AL 36644

(Request First Delivery)