



**ARTHUR R. OUTLAW CONVENTION CENTER
KITCHEN FLOORING REPLACEMENT
Mobile Alabama
CN-26-23**

June 2, 2023

SECTION 009003-ADDENDUM 03

PART 1 - GENERAL

1.1 GENERAL

- A. This addendum forms a part of the Contract Documents and modifies the original Bidding Documents as noted below. Acknowledge receipt of this Addendum in the space provided on the Bid Form. Failure to do so may subject the Bidder to disqualification.
- B. This addendum consists of 3 pages and one (1) attachment as listed in this Addendum.
- C. Drawings:
 - 1. Sheets identified in this Addendum as “Re-issued” shall replace previously issued Sheets, with the same Sheet Number, with Sheets attached to this Addendum.

1.2 NOTICE TO BIDDERS

- A. This Addendum is issued pursuant to the Instructions to Bidders and Conditions of the Contract. This Addendum serves to clarify, revise, and supersede information in the Project Manual, Drawings, and previously issued Addenda. Portions of the Addendum affecting the Contract Documents will be incorporated into the Contract by enumeration of the Addendum in the Owner/Contractor Agreement.
- B. **The date, time of day and location for delivery of Bids is unchanged from that contained in the previous Addendum.**

PART 2 - REVISIONS TO DIVISION 00 AND 01 (NA)

PART 3 - REVISIONS TO DIVISIONS 02 - 49 SPECIFICATION SECTIONS

- 3.1 Section 096723_Resinous Flooring, R1 AD03 dated June 2, 2023. Change as follows: (not reissued)
- A. Article 1.8, A.: In two places change “(1)” to (3) three.
 - B. Article 2.1, A.: Add the following:
 - 1. Dex-O-Tex, Tek-Crete-TT, with, Tek-Crete-CP with all other comparable materials appropriate to the requirements
 - C. Article 2.1: Add the following:
 - F. Integral Wall Base: Construct integral wall base using same or comparable materials as used for resinous flooring.
 - 1. Select materials based on flooring manufacturer’s recommendations for in service use equal to or greater than flooring including flooring’s physical properties and finish color.
 - D. Article 2.2: Add the following”
 - C. Joint Sealant For Use In Cooler Freezer: Type recommended or produced by resinous flooring manufacturer, approved for food contact with in service use recommended for five degrees Fahrenheit below zero or lower.
 - D. Metal Cap Trim: Metal trim in configuration recommended by manufacturer. Metal shall have physical properties for corrosion and chemical resistance not less than Type 316 Stainless steel.

PART 4 - REVISIONS TO DRAWING SHEET

- 4.1 General: Provide resinous base at interior and exterior of all cooler/freezers. Reference Sheet A500
- 4.2 Sheet A500: Re-issued as attachment to this Addendum.

PART 5 - ATTACHMENTS

5.1 DRAWING SHEETS

- A. Sheet A500, dated April 26, 2023: Re-issued as Revision 1, dated June 2, 2023.

END OF DOCUMENT

